**Specification Sheet** 

# ABB Welcome<sup>™</sup> IP Gateway 83342-500

## 83342-500

## **IP Gateway**

The IP Gateway enables integration of smartphones and devices (iOS and Google's Android™) to the door entry system. The IP-Gateway has a user interface that can be reached via an Internet browser.


## **Key features**

- Supports remote access to door entry system through WLAN and internet.
- Its PC interface can be used to program telephone gateway.

# ((f

### Overview of control buttons

Number	Function
1	Status LED
2	LAN connection
3	System controller input (a, b)
4	Floor call button



## **Specifications**

Operating temperature: 23 °F to -113 °F

Single-wire clamps:  $2 \times 0.28 \text{ mm}^2 - 2 \times 1 \text{ mm}^2$ Fine-wire clamps:  $2 \times 0.28 \text{ mm}^2 - 2 \times 1 \text{ mm}^2$ 

Bus voltage (a, b): 20-30 VDC (Supplied by system controller or auxiliary power supply)

Mount: DIN rail mounted (DIN EN 50022)

Flammability: UL 94 V0

Product dimensions: 3.54" x 5.67" x 2.56"

## Contact us

## **ABB**

Low Voltage Products 8155 T&B Boulevard Memphis, TN 38125 www.abb.us/lowvoltage

USA Technical Support: 888-862-3289 Customer Service: 888-862-3290

7:00 a.m. – 5:30 p.m., CST, Monday – Friday

techsupport@tnb.com