



ALL VALVES ARE CERTIFIED TO NSF/ANSI 372 FOR USE WITH POTABLE WATER

Model	Valve Size	A	B	C	D	E	F	G	H	Flow GPM
WCDACTDUAL	-	-	-	-	.74	3.78	4.10	5.00	4.05	-
WCDACTDUAL	1/2	1/2 - 14 NPT	2.60	4.78	.74	3.78	4.10	5.00	4.05	19
WCDACTDUAL	3/4	3/4 - 14 NPT	2.90	5.02	.74	3.78	4.10	5.00	4.05	34
WCDACTDUAL	1	1 - 11-1/2 NPT	3.56	5.19	.74	3.78	4.10	5.00	4.05	52
WCDACTDUAL	1-1/4	1-1/4 - 11-1/2 NPT	3.66	5.18	.74	3.78	4.10	5.00	4.05	77

Enclosure: Polycarbonate
 Power: Power Converter With 20' Cord
 Controls: Local Controls
 Valve: Full Port Brass Ball Valve
 Frequency: 418 MHz

UNCONTROLLED DRAWING

THIS PRINT IS THE PROPERTY OF DYNAQUIP CONTROLS AND SHALL NOT BE COPIED, REPRODUCED, LOANED, OR DISPOSED OF DIRECTLY OR INDIRECTLY, NOR USED FOR ANY PURPOSE OTHER THAN THAT FOR WHICH IT IS SPECIFICALLY FURNISHED EXCEPT BY WRITTEN PERMISSION OF DYNAQUIP CONTROLS.

NO. **WCDACTDUAL** FILE NO. SUB391

TITLE
Actuator shown with valve attached

DR MJP	DATE 07-17-19	CHKD MJP	DATE 03-07-17	ENGR MJP	DATE 032-07-17
-----------	------------------	-------------	------------------	-------------	-------------------

