

# JA Audio Speakers



ROCK-RK820 (Outdoor)

Power Handling: 250  
 Frequency: 100 Hz ~ 22kHz 3 dB  
 Color: Grey or Red  
 Cone Type and Size: 8" Black Polypropylene Cone  
 Tweeter: 2" Polypropylene  
 Impedance: 8  $\Omega$ nominal, 6 $\Omega$ minimum  
 Warranty: IntraSonic 2 Year



JA-SS12

Power Handling: 260  
 Frequency: 20 Hz to 300 Hz  
 Overall Dimensions: 21" (W) x 21" (D) x 21" (H)  
 Cone Type and Size: 12" Long-Throw Woofer to Reproduce Low Frequency's  
 Bass Booster: 20 Hz + 5dB  
 Frequency: 20 Hz to 300 Hz  
 Auto power input signal level: 5mv  
 Impedance: 8  $\Omega$ nominal  
 Warranty: IntraSonic 2 Year



B3-HTPACK (B3W)

5.1 Mini-Cube Surround Sound  
 Includes: (5) Each JA-B3 Mini Cubes  
 (1) JA-SS10 Subwoofer  
 (1) I51W Home Theater Wall Plate  
 Colors: White or Black Mini-Cubes



JA-SS10

Power Handling: 120 (200 Watts Max)  
 Frequency: 50Hz ~ 400Hz  
 Overall Dimensions: 14.5" (W) x 14.5" (D) x 15" (H)  
 Cone Type and Size: 10" Long-Throw Woofer to Reproduce Low Frequency's  
 Bass Booster: 20 Hz + 5dB  
 Frequency: 50Hz ~ 400Hz  
 Auto power input signal level: 5mv  
 Impedance: 8  $\Omega$ nominal  
 Warranty: IntraSonic 2 Year



B2-HTPACK (B2W)

5.1 Diamond Mini-Cube Surround Sound  
 Includes: (5) Each JA-B3 Diamond Mini Cubes  
 (1) JA-SS7 Subwoofer  
 (1) I51W Home Theater Wall Plate  
 Colors: White or Black Diamond Mini-Cubes



JA-SS7

Power Handling: 80 (120 Watts Max)  
 Frequency: 55Hz ~ 600Hz  
 Overall Dimensions: 9 7/8" x 14" x 13"  
 Cone Type and Size: 6x9" Long-Throw Woofer to Reproduce Low Frequency's  
 Bass Booster: 20 Hz + 5dB  
 Frequency: 18 dB High - Low Pass  
 Auto power input signal level: 5mv  
 Impedance: 8  $\Omega$ nominal  
 Warranty: IntraSonic 2 Year

## IntraSonic Builder Tech Speakers, Subwoofer & Mounting Brackets Priced to sell without giving up the quality



Model I30C

Power Handling: 30  
 Mounting: Cam-Lock  
 Grille: White Metal  
 Frequency: 48 Hz - 20 KHz  
 Overall Dimensions: 9 1/2" D  
 Install Dimensions: 7 1/2" D  
 Tweeter Type and Size: Mylar 13mm  
 Magnet Weight: 10 oz  
 Cone Type and Size: 6 1/2" Coated Paper  
 Db Sensitivity: 88db  
 Impedance: 8  $\Omega$ nominal  
 Speaker Bracket: SPKBKT-6C  
 Warranty: IntraSonic 10 Year



Model I100C

Power Handling: 100  
 Mounting: Cam-Lock  
 Grille: White Metal  
 Frequency: 36 Hz - 22 KHz  
 Overall Dimensions: 10 3/4" D  
 Install Dimensions: 9 1/4" D  
 Tweeter Type and Size: 360° Directional Laminated Alum PP1  
 Magnet Weight: 13.3 oz  
 Cone Type and Size: 8" Laminated PP  
 Db Sensitivity: 89db  
 Impedance: 8  $\Omega$ nominal  
 Bass and Treble: 3 Position Adjustable  
 Speaker Bracket: SPKBKT-8C  
 Warranty: IntraSonic 10 Year



Model I125SW

Power Handling: 125  
 Frequency: 28 Hz - 200 KHz  
 Woofer Type and Size: 10" Rigid-Balanced  
 Magnet Weight: 5.5 lbs  
 Cone Type and Size: 6 1/2" Coated Paper  
 Overall Dimensions: 19 1/4" x (H) x 12 1/4" W x 17 5/8" (D)  
 Crossover: Variable 50 - 200Hz  
 Cabinet: MDF Laminated Wood  
 Grain Vinyl  
 On/Off: Automatic or Manual Line Level  
 Input / Output: Line Input  
 Warranty: IntraSonic 2 Year



Model I30W

Watts/RMS: 30  
 Mounting: Cam-Lock  
 Grille: White Metal  
 Frequency: 48 Hz - 20 KHz  
 Overall Dimensions: W 8 3/4" X H 12"  
 Install Dimensions: W 7 3/8" X H 10 3/4"  
 Tweeter Type and Size: Mylar 13mm  
 Magnet Weight: 10 oz  
 Cone Type and Size: 6 1/2" Coated Paper  
 Db Sensitivity: 88db  
 Impedance: 8  $\Omega$ nominal  
 Speaker Bracket: SPKBKT-61W  
 Warranty: IntraSonic 10 Year



Model I100W

Watts/RMS: 100  
 Mounting: Cam-Lock  
 Grille: White Metal  
 Frequency: 36 Hz - 22 KHz  
 Overall Dimensions: W 10" X H 14 1/4"  
 Install Dimensions: W 8 7/8" X W 12 7/8"  
 Tweeter Type and Size: 360° Directional Laminated Alum PP1  
 Magnet Weight: 13.3 oz  
 Cone Type and Size: 8" Laminated PP  
 Db Sensitivity: 89db  
 Impedance: 8  $\Omega$ nominal  
 Bass and Treble: 3 Position Adjustable  
 Speaker Bracket: SPKBKT-81W  
 Warranty: IntraSonic 10 Year



Part Number - SpeakerLit

# We Will Blow Your Grills Off!



You have to  
**hear to believe**



New Silver Series  
**Designed to Perform**



The Ultimate  
**Acoustic Innovation**

# JA Audio Speakers



EX-180

Power Handling: 45~150  
 Mounting: Cam-Lock  
 Grille: White Aluminum  
 Frequency: 45 Hz - 22,000Hz  
 Overall Dimensions: 14 1/8" x 10 1/8" x 4"  
 Install Dimensions: 12 3/4" x 8 3/4"  
 Cone Type and Size: 8" Yellow Fiberglass Cone with a Rubber Surround  
 Crossover: Hi-End 12 dB, Adjustable for Tweeter & Midrange Level ±3dB  
 Tweeter: 1" Titanium Dome Swivel  
 Efficiency: 88db  
 Impedance: 8 Ωnominal, 6Ωminimum  
 Speaker Bracket: SPKBKT-81W  
 Warranty: IntraSonic 10 Year



EX-308C

Power Handling: 45~150  
 Mounting: Cam-Lock  
 Grille: White Aluminum  
 Frequency: 45 Hz - 22,000Hz  
 Overall Dimensions: 11" x 6 1/2" x 10"  
 Cone Type and Size: 8" Yellow Fiberglass Cone with a Rubber Surround  
 Crossover: Hi-End 12 dB, Adjustable for Tweeter & Midrange Level ±3dB  
 Tweeter: 1" Titanium Dome Swivel  
 Efficiency: 88db  
 Impedance: 8 Ωnominal, 6Ωminimum  
 Mid-Range: 2.5" Yellow Fiberglass Cone Mid-Range  
 Speaker Bracket: N/A  
 Warranty: IntraSonic 10 Year



EX-206C

Power Handling: 5~100  
 Mounting: Cam-Lock  
 Grille: White Aluminum  
 Frequency: 55Hz - 22,000Hz  
 Overall Dimensions: 9 1/8" x 5 1/4" x 8 3/8"  
 Cone Type and Size: 6.5" Yellow Fiberglass Cone with a Rubber Surround  
 Crossover: Hi-End 18 dB, Adjustable for Tweeter Level ±3dB  
 Angel Degree: 20  
 Tweeter: 1" Titanium Dome Swivel  
 Efficiency: 89db  
 Impedance: 8 Ωnominal, 6Ωminimum  
 Speaker Bracket: SPKBKT-6C  
 Warranty: IntraSonic 10 Year




JA-16AII

Power Handling: 10~100  
 Mounting: Cam-Lock  
 Grille: White Metal  
 Frequency: 50 Hz - 22,000Hz  
 Overall Dimensions: 8 3/4" x 12 1/16" x 3 1/4"  
 Install Dimensions: 7 1/4" x 10 11/16"  
 Cone Type and Size: 6 1/2" Aluminum Cone with a Rubber Surround  
 Crossover: 24 dB High - Low pass  
 Tweeter: 1" Aluminum Dome Swivel With Ferrofluid Cooled Voice Coil  
 Efficiency: 90db  
 Impedance: 8 Ωnominal, 6Ωminimum  
 Speaker Bracket: SPKBKT-61W  
 Warranty: IntraSonic 10 Year



JA-C6AII

Power Handling: 10~100  
 Mounting: Cam-Lock  
 Grille: White Aluminum  
 Frequency: 50 Hz - 22,000Hz  
 Overall Dimensions: 9 1/2" x 3 1/8" x 8"  
 Cone Type and Size: 6 1/2" Aluminum Cone Woofer with a Rubber Surround  
 Crossover: 18 dB High - Low pass  
 Tweeter: Tweeter 0/-3 dB  
 Efficiency: 89db  
 Impedance: 8 Ωnominal  
 Speaker Bracket: SPKBKT-6C  
 Warranty: IntraSonic 10 Year



EX-R6T

Power Handling: 5~100  
 Mounting: Cam-Lock  
 Grille: White Aluminum  
 Frequency: 52 Hz - 22,000Hz  
 Overall Dimensions: 11" x 6" x 9 1/2"  
 Cone Type and Size: Pivoting 6.5" Yellow Fiberglass Cone with a Rubber Surround  
 Crossover: Hi-End 12 dB, Adjustable for Tweeter & Woofer Level ±3dB  
 Tweeter: Pivoting 1" Titanium Dome Swivel  
 Efficiency: 88db  
 Impedance: 8 Ωnominal, 6Ωminimum  
 Speaker Bracket: SPKBKT-8C  
 Warranty: IntraSonic 10 Year



EX-C80

Power Handling: 45~150  
 Mounting: Cam-Lock  
 Grille: White Aluminum  
 Frequency: 45 Hz - 20,000Hz  
 Overall Dimensions: 11" x 5 3/4" x 9 1/2"  
 Cone Type and Size: 8" Yellow Fiberglass Cone with a Rubber Surround  
 Crossover: Hi-End 12 dB, Adjustable for Tweeter & Woofer Level ± 3dB  
 Tweeter: 1" Titanium Dome Swivel  
 Efficiency: 88db  
 Impedance: 8 Ωnominal, 6Ωminimum  
 Mid-Range: 2.5" Yellow Fiberglass Cone Mid-Range  
 Speaker Bracket: SPKBKT-8C  
 Warranty: IntraSonic 10 Year



EX-C65

Power Handling: 5~100  
 Mounting: Cam-Lock  
 Grille: White Aluminum  
 Frequency: 50 Hz - 22,000Hz  
 Overall Dimensions: 9" x 4" x 8"  
 Cone Type and Size: 6.5" Yellow Fiberglass Cone with a Rubber Surround  
 Crossover: Hi-End 18 dB, Adjustable for Tweeter & Woofer ±3dB  
 Tweeter: 1" Titanium Dome Swivel  
 Efficiency: 90db  
 Impedance: 8 Ωnominal, 6Ωminimum  
 Speaker Bracket: SPKBKT-6C  
 Warranty: IntraSonic 10 Year



JA-D2 (D2W)

Power Handling: 10~100  
 Mounting: Fixed Bracket Included  
 Frequency: 170Hz - 20kHz  
 Colors: White or Black  
 Dimensions: 2 1/2" x 5 1/4" x 3"  
 Driver: 2" Full Range x 2  
 Sensitivity: 89 dB 1W/1M  
 Impedance: 6Ωminimum  
 Warranty: IntraSonic 10 Year



JA-B3 (B3W)

Power Handling: 100 (35 Watts Continuous)  
 Mounting: Adjustable Swivel Bracket Included  
 Frequency: 250 Hz - 18kHz  
 Colors: White or Black  
 Dimensions: 3 1/4" x 7" x 4 3/4"  
 Sensitivity: 91 dB/Wm  
 Impedance: 6Ωminimum  
 Warranty: IntraSonic 10 Year



JA-T5 (T5W) Outdoor

Power Handling: 20~120  
 Mounting: Bracket  
 Frequency: 50 Hz - 22,000Hz  
 Colors: White  
 Overall Dimensions: 7 1/16" x 9 11/16" x 6 9/16"  
 Cone Type and Size: 5 1/4" polypropylene with a Rubber Surround  
 Tweeter: 5/8" liquid-cooled polycarbonate  
 Sensitivity: 89 dB 1W/1M  
 Impedance: 8Ωminimum  
 Warranty: IntraSonic 2 Year



EX-I65

Power Handling: 5~100  
 Mounting: Cam-Lock  
 Grille: White Aluminum  
 Frequency: 50 Hz - 22,000Hz (+/- 3db)  
 Overall Dimensions: 8 3/4" x 12 1/2" x 3 1/2"  
 Install Dimensions: 7 1/2" x 10 3/8"  
 Cone Type and Size: 6.5" Yellow Fiberglass Cone with a Rubber Surround  
 Crossover: Hi-End 18 dB, Adjustable for Tweeter & Woofer Level ±3dB  
 Tweeter: 1" Titanium Dome Swivel  
 Efficiency: 90db  
 Impedance: 8 Ωnominal, 6Ωminimum  
 Speaker Bracket: N/A  
 Warranty: IntraSonic 10 Year



EX-CC6

Power Handling: 35~100  
 Mounting: Cam-Lock  
 Grille: White Aluminum  
 Frequency: 52 Hz - 22,000Hz  
 Overall Dimensions: 20 3/4" x 9" x 4"  
 Install Dimensions: 18 3/4" x 7 3/8"  
 Cone Type and Size: (2) 6 1/2" Yellow Fiberglass Cone with a Rubber Surround  
 Crossover: Hi-End 12 dB, Adjustable for Tweeter & Woofer Level ±3dB  
 Tweeter: 1" Titanium Dome Swivel  
 Efficiency: 88db  
 Impedance: 8 Ωnominal, 6Ωminimum  
 Speaker Bracket: N/A  
 Warranty: IntraSonic 10 Year



JA-CC5AII

Power Handling: 10~100  
 Mounting: Cam-Lock  
 Grille: White Aluminum  
 Frequency: 70 Hz - 22,000Hz  
 Overall Dimensions: 17 3/4" x 8 3/4" x 3"  
 Install Dimensions: 16 3/8" x 7 3/8"  
 Cone Type and Size: (2) 5 1/4" Aluminum Cone with a Rubber Surround  
 Crossover: 18 dB High - Low Pass  
 Tweeter: Tweeter 0/-3 dB  
 Efficiency: 89db  
 Impedance: 8 Ωnominal  
 Speaker Bracket: N/A  
 Warranty: IntraSonic 10 Year



JA-SC6

Power Handling: 100  
 Selector Type: Push Button  
 Frequency: 20 Hz - 22kHz  
 Colors: Black  
 Speakers support: 6 pairs/4 Ohm Minimum  
 Overall Dimensions: 1 7/8" x 11 1/2" x 6 7/8"  
 Warranty: IntraSonic 2 Year



JA-VNB-75

Power Handling: 75 RMS/150 Max  
 Attenuation: 34-0 dB in 12 position  
 Frequency: 35 Hz - 20kHz  
 Colors: White  
 Overall Dimensions: 14 1/8" x 10 1/8" x 4"  
 Warranty: IntraSonic 2 Year



JA-VSL-100

Power Handling: 100 RMS/180 Max  
 Attenuation: 34-0 dB in 12 position  
 Frequency: 35 Hz - 20kHz  
 Colors: White  
 Warranty: IntraSonic 2 Year



JA-I8AII

Power Handling: 10~150  
 Mounting: Cam-Lock  
 Grille: White Metal  
 Frequency: 42 Hz - 22,000Hz  
 Overall Dimensions: 14 1/16" x 14 1/16" x 3 1/4"  
 Install Dimensions: 8 3/4" x 12 7/8"  
 Cone Type and Size: 8" Aluminum Cone Woofer with a Rubber Surround  
 Crossover: 24dB High - Low pass  
 Tweeter: 1" Titanium Dome Swivel  
 Efficiency: 90db  
 Impedance: 8 Ωnominal, 6Ωminimum  
 Speaker Bracket: SPKBKT-81W  
 Warranty: IntraSonic 10 Year




JA-C8AII

Power Handling: 10~150  
 Mounting: Cam-Lock  
 Grille: White Aluminum  
 Frequency: 42 Hz - 22,000Hz  
 Overall Dimensions: 11" x 3 1/2" x 9 1/2"  
 Install Dimensions: 9 1/2" x 3 1/2"  
 Cone Type and Size: 8" Aluminum Cone with a Rubber Surround  
 Crossover: 18dB High - Low pass  
 Tweeter: Tweeter 0/-3 dB  
 Efficiency: 91db  
 Impedance: 8 Ωnominal, 6Ωminimum  
 Speaker Bracket: SPKBKT-8C  
 Warranty: IntraSonic 10 Year



(6C) Dimension 8"  
 (8C) Dimension 9 5/8"



(6IW) Dimension 10 3/4" x 7 3/8"  
 (8IW) Dimension 12 7/8" x 8 7/8"