

Switches and Buttons

Tamper Switches

SS-072Q For normally closed tamper circuits

SS-073Q For normally open tamper circuits

- For drawers and alarm boxes
- Silver-plated contacts
- Rated 0.5A@24VDC



Toggle Switch

SS-076Q/SW Snow-white

- SPST Toggle switch rated 3A@125VDC
- Attractive plastic case with two screw holes
- Pre-wired 6" (15cm) leads



Momentary Push Buttons

SS-032Q/RD Red N.O. button

SS-033Q/BK Black N.C. button

- Fits 1/2" (13mm) hole
- Rated 1A@12VDC



SS-032Q/RD



SS-033Q/BK

Foil Connection Block

SS-202Q

- Double-blocked
- Self-adhesive mounting
- Ramped metal plate reduces foil breaks



Hold-up Buttons

SS-077Q N.C. Push-to-open operation

SS-078Q N.O. Push-to-close operation

- Latching push button, flag shows when pressed
- High-impact ABS case, stainless steel cover
- SPST Switch rated 1A@12VDC
- Two reset keys included



Vibration Shock Sensors

SS-040Q/BR N.C., brown

SS-040Q/W N.C., white

- Detects shock to window glass, walls, or ceiling
- Gold-plated contacts for longer life and reliability
- Built-in tamper switch for complete security
- Adjustable from 1~50 g
- 1@50VDC
- Size: 2³/₈"x1³/₁₆"x5⁵/₈"



SS-040Q/BR



SS-040Q/W

Momentary Push Button

SS-074/BG N.O. Push-to-close operation

- Double-button operation virtually eliminates accidental triggering
- Sturdy, metal case, silver-plated SPST contacts, pre-wired for quick installation
- Rated 1A@25VDC



SECO-LARM® U.S.A., Inc.

16842 Millikan Avenue, Irvine, CA 92606

Phone: (949) 261-2999 | (800) 662-0800 Fax: (949) 261-7326

Website: www.seco-larm.com Email: sales@seco-larm.com



Copyright © 2019 SECO-LARM U.S.A., Inc. All rights reserved.
All trademarks are the property of SECO-LARM U.S.A., Inc. or their respective owners.
The SECO-LARM policy is one of continual development. For that reason, SECO-LARM reserves the right to change prices and specifications without notice. SECO-LARM is not responsible for misprints.

SECO-LARM® ENFORCER® CRIMEBUSTER® CBA® SLI®

PI_SS-xxxx_190523_ML.docx

Interruptores y Botones

Interruptores de Sabotaje

SS-072Q Para circuitos de sabotaje normalmente cerrados

SS-073Q Para circuitos de sabotaje normalmente abiertos


- Para cajones y cajas de alarma
- Contactos chapados en plata
- Clasificado 0.5A@24V C.C.



Interruptor de Enganche

SS-076Q/SW Blanco como la nieve

- Interruptor de palanca SPST clasificado 3A@125V C.C.
- Atractiva caja de plástico con dos agujeros para tornillos
- Cables de 6" (15 cm) precableados



Botones Pulsadores Momentáneos

SS-032Q/RD Botón rojo N.A.

SS-033Q/BK Botón negro N.C.

- Se adapta a un agujero de 1/2" (13 mm)
- Clasificado 1A@12V C.C.



SS-032Q/RD

SS-033Q/BK

Bloque de Conexión de Lámina

SS-202Q

- Doble bloqueo
- Montaje autoadhesivo
- La placa de metal rampante reduce las roturas de la lámina



SECO-LARM® U.S.A., Inc.

16842 Millikan Avenue, Irvine, CA 92606

Phone: (949) 261-2999 | (800) 662-0800 Fax: (949) 261-7326

Website: www.seco-larm.com Email: sales@seco-larm.com

Botones de Retención

SS-077Q N.C. Operación de presionar para abrir

SS-078Q N.A. Operación de presionar para cerrar

- Pulsador de enganche, la bandera muestra cuando se presiona
- Caja de ABS de alto impacto, cubierta de acero inoxidable.
- Interruptor SPST clasificado 1A@12V C.C.
- Dos llaves de reinicio incluidas



Sensores de Vibración de Choque

SS-040Q/BR N.C., marrón

SS-040Q/W N.C., blanco

- Detecta choques en vidrios de ventanas, paredes o techos
- Contactos chapados en oro para una vida útil más larga y confiabilidad
- Interruptor de manipulación incorporado para una seguridad completa
- Ajustable de 1~50 g
- 1@50V C.C.
- Tamaño: 2³/₈"x1³/₁₆"x5⁵/₈"



SS-040Q/BR

SS-040Q/W

Botones Pulsadores Momentáneo

SS-074/BG N.A. Operación de presionar para cerrar

- La operación de doble botón virtualmente elimina el disparo accidental
- Caja de metal robusta, contactos SPST bañados en plata, precableados para una instalación rápida
- Clasificado 1A@25V C.C.

