

# PK502B Dual Entrance Control Unit IL955 Specification Sheet

#### Tek-ENTRY® Apartment Entry Systems • Rev. 2 - 11/2016

### **Features**

- Provides access control to multiple entrances on one apartment entry system
- Use with PK543A speaker systems or PK205 handset systems
- Transfers both door release function and audio between entrance panels
- Powered by the intercom system amplifier
- Polarized plug-in color-coded pigtailed connector
- Built-in test circuit with LED display
- Surface mounted
- Small footprint

## **Description**

The TekTone<sup>®</sup> PK502B Dual Entrance Control Unit provides a means to transfer apartment intercom panel and door release operations between more than one entrance. Pressing a call button on an entrance panel automatically transfers the voice and door release functions to that entrance. All PK502B control units are located at the amplifier location and do not need to be spread out.



#### **PK502B Dual Entrance Control Unit**

### **Specifications**

Dimensions:	Height:	5.5" (140 mm)
	Width:	3.125" (80 mm)
	Depth:	2" (51 mm)
Construction:	Flame-retardant (UL® 94V-0) plastic	
Connections:	Polarized plug-in type	
Mounting:	Surface mount	

### **Required Components**

PK543A Amplifier/Relay/Power Supply -or-PK205 Amplifier/Relay/Power Supply

#### www.tektone.com

324 Industrial Park Road • Franklin, NC 28734 • tektone@tektone.net Phone: 828.524.9967 • Fax: 828.524.9968 • Sales: Choose option 2 • Tech Support: Choose option 3 TekTone's quality system is registered by DQS to the ISO 9001 standard. (Reference #10001510.)